



How to configure API & CLI access for mCloud

Vincent (Vinnie) Curle - 2026-01-07 - [mCloud](#)

Overview

This guide contains an overview of how you can use the OpenStack CLI client with a TOTP (Time-based One-Time Password) enabled user, or for a machine-user with the API services in your mCloud Dashboard.

CLI Access for a TOTP-Enabled User

For standard users, you can use the TOTP-enabled OpenStack client to authenticate. Download the client from the GitHub repository below and follow the instructions in the README file to complete the setup:

<https://github.com/micron21/totp-capable-openstack-client-for-mcloud/>

API Access for a Machine User

Prerequisite: As Machine users are unable to log into the mCloud Dashboard, you will need to [contact the Micron21 Support Team](#) to request a new machine user for mCloud API access, and supply the static public IP address the machine user will connect from and request a new machine user for mCloud API access. Once confirmed, you will be provided with a specific API-enabled user.

Method

Installing and configuring the OpenStack CLI Client

1. Using the link below, install the OpenStack CLI client on your preferred workstation
 1. <https://docs.openstack.org/newton/user-guide/common/cli-install-openstack-command-line-client-s.html>
2. Log in to your mCloud Dashboard (<https://mcloud.micron21.com>)
3. At the top right, click your user, then click "OpenStack RC file" and save/copy the contents of the file to your workstation.
4. When you want to use the client, load the RC file by running "source admin-openrc.sh" or "source project-name-openrc.sh" as required and enter your user's password when you are prompted for credentials
5. You can now use the OpenStack CLI client via the API
 1. Note: Each time you create a new session (terminal, ssh, etc), you will need to re-run the source command to load the environment variables.

Issuing a custom keystone token

Sometimes, when making changes via CLI or Postman/curl and testing, you will need an authentication token.

Once you have set up your OpenStack client, you can issue a token, example below:

```
# openstack token issue
+-----+-----+
| Field | Value
+-----+-----+
| expires | 2024-11-14T10:02:55+0000
| id | { HERE WILL BE YOUR TOKEN}
| project_id | cb58ecXXXXXXXXXXXXXXXXXXXX38e06
| user_id | 5c9495XXXXXXXXXXXXXXXXXXXXfcd50
+-----+-----+
```

You can also curl directly against Keystone, with a few more arguments. More information from the official documentation: https://docs.openstack.org/keystone/latest/api_curl_examples.html

Once added, you can use that token when issuing Curl commands.

Using a custom keystone token against an API endpoint

Here's an example of using a token against the Octavia Load Balancer Service API endpoint.

```
curl -g -i -X GET https://mcloud.micron21.com:9876/v2.0/lbaas/loadbalancers -H
"Accept: application/json" -H "User-Agent: openstacksdk/3.0.0 keystoneauth1/5.6.0
python-requests/2.31.0 CPython/3.12.3" -H "X-Auth-Token: { HERE PUT YOUR TOKEN }"
```

e.g.

```
curl -g -i -X GET https://mcloud.micron21.com:9876/v2.0/lbaas/loadbalancers -H
"Accept: application/json" -H "User-Agent: openstacksdk/3.0.0 keystoneauth1/5.6.0
python-requests/2.31.0 CPython/3.12.3" -H "X-Auth-Token:
gAAAAAXXXXXXXXXXXXXXXXXXatbj0j8ZRowhsK-g416Ky7zXJfiPQqDdYje6y-Y2nPQBefh3Rfezlk3zc0-
CFwFZfUHvfuWXXXXXXXXXXXXXXXXXuvCpqHhmtvXWpnr-x0ygulB_swXXXXXXXXXXXXXoS-
Q6yfZSTncXMYjxraTN0"
```

returns:

```
HTTP/2 200
date: Wed, 13 Nov 2024 23:20:56 GMT
server: Apache/2.4.52 (Ubuntu)
x-openstack-request-id: req-7998fd45-e91e-4b6e-8c4c-8759152821cd
content-type: application/json
content-length: 48

{"loadbalancers": [], "loadbalancers_links": []}
```

Keystone and API flowchart image example

